


Unsplit long arm



Split long arm

Range: 1700 Kg - 2500 Kg

- Rotating paper roll clamp for safe and effective vertical and horizontal roll handling.
- Slim and smooth arm and frame design, optimal visibility and advanced hydraulic operation.
- Pivoting arm movement. Short and long arms. Non-split long arm for single roll handling. Split arm for 1 - 2 roll handling.
- 180-degree rotation. Hydraulic cushioning in the vertical end positions.
- All hydraulic functions protected with built-in pressure relief valves and check valves. All service and maintenance points easily available.

Model	Capacity	Load Centre	Roll Range	Height	Weight	Horizontal Centre of Gravity	Vertical Centre of Gravity	Effective Thickness	Contact Pads	Contact Pad Gap	Mounting Height	Mounting Class
	Q kg	BP mm	A mm	D mm	W Kg	HCG mm	VCG mm	LL mm	M x N mm	O mm	H mm	ISO 2328
Single roll clamps - Unsplit long arm												
AR-25RH-13F	2500	650	550-1300	830	720	232	360	190	220x300	200	60	2 / 3 A
AR-25RH-13	2500	650	250-1300	830	725	232	360	190	220x300	200	60	2 / 3 A
AR-25RH-14F	2200	700	600-1400	830	740	257	360	190	220x300	200	60	2 / 3 A
AR-25RH-14	2200	700	250-1400	830	745	257	360	190	220x300	200	60	2 / 3 A
AR-25RH-15F	2100	760	650-1520	830	760	287	360	190	220x300	200	60	2 / 3 A
AR-25RH-15	2100	760	260-1520	830	765	287	360	190	220x300	200	60	2 / 3 A
AR-25RH-16F	2000	800	700-1600	830	770	300	360	190	220x300	200	60	2 / 3 A
AR-25RH-16	2000	800	270-1600	830	775	300	360	190	220x300	200	60	2 / 3 A
AR-25RH-18F	1700	915	800-1830	830	820	358	360	200	220x300	200	60	2 / 3 A
AR-25RH-18	1700	915	400-1830	830	825	358	360	200	220x300	200	60	2 / 3 A
1 - 2 roll clamps - Split long arm												
AR-25RJ-13F	2500	650	550-1300	830	710	226	360	190	220x300	200	60	2 / 3 A
AR-25RJ-13	2500	650	250-1300	830	715	226	360	190	220x300	200	60	2 / 3 A
AR-25RJ-14F	2200	700	600-1400	830	730	250	360	190	220x300	200	60	2 / 3 A
AR-25RJ-14	2200	700	250-1400	830	735	250	360	190	220x300	200	60	2 / 3 A
AR-25RJ-15F	2100	760	650-1520	830	755	279	360	190	220x300	200	60	2 / 3 A
AR-25RJ-15	2100	760	260-1520	830	760	279	360	190	220x300	200	60	2 / 3 A
AR-25RJ-16F	2000	800	700-1600	830	760	292	360	190	220x300	200	60	2 / 3 A
AR-25RJ-16	2000	800	270-1600	830	765	292	360	190	220x300	200	60	2 / 3 A
AR-25RJ-18F	1700	915	800-1830	830	810	350	360	200	220x300	200	60	2 / 3 A
AR-25RJ-18	1700	915	400-1830	830	815	350	360	200	220x300	200	60	2 / 3 A

Notes:

- Two hydraulic functions required.
- Models AR-25RHF/RJF with fixed (non-moving) short arm.
- Models AR-25RH/RJ with hydraulically positionable short arm.
- Standard contact pads: cast pad with high-friction surface.
- Minimum 5-degree forward tilt on lift mast is required for horizontal handling.
- For 0-degree tilt, special arms are available. Consult Bolzoni Auramo

Options:

- Special roll ranges.
- Arm height D = 1035 mm.
- Contact pad options:
 - steel-sprayed
 - rubber faced
 - polyurethane faced
 - full length contact pads.

